

## FATTY FOOD DELIVERY HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
<b>RGD-013</b>	1/2"	12.7	23.0	10	30	0.332	30
<b>RGD-019</b>	3/4"	19.0	30.0	10	30	0.492	30
<b>RGD-025</b>	1"	25.4	36.0	10	30	0.590	30
<b>RGD-032</b>	1-1/4"	31.8	43.0	10	30	0.769	30
<b>RGD-038</b>	1-1/2"	38.1	50.0	10	30	0.977	30
<b>RGD-050</b>	2"	50.8	63.0	10	30	1.249	30
<b>RGD-065</b>	2-1/2"	63.5	76.0	10	30	1.326	30
<b>RGD-075</b>	3"	76.2	89.0	10	30	1.625	30
<b>RGD-100</b>	4"	101.6	116.0	10	30	2.330	30
<b>RGD-150</b>	6"	152.0	168.0	10	30	3.569	30

### APPLICATION

Softwall hose for delivery of food products, particularly suitable for oil and fatty foods.

### CONSTRUCTION

**Tube:** White color of food grade NBR blend compound. Cream and alcohol resistance.

**Cover:** Blue color of food grade NBR blend compound. Abrasion and ozone resistance.

**Reinforcement:** Multiple layers of high tensile synthetic cord.

**Sanification :** max 150°C for a few minutes with steam; max 60°C for a few minutes with 2% nitric acid, 2% peracetic acid, 2% phosphoric acid, 5% caustic soda

**Temperature:** -20°C to +80°C

**Safety Factor:** 3:1