

## LAYFLAT WATER DISCHARGE HOSE 5 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
WLFM-05-019	3/4"	19.0	28.0	5	15	0.420	30
WLFM-05-025	1"	25.4	35.0	5	15	0.588	30
WLFM-05-032	1-1/4"	31.8	40.0	5	15	0.643	30
WLFM-05-038	1-1/2"	38.1	48.0	5	15	0.872	30
WLFM-05-050	2"	50.8	60.0	5	15	0.992	30
WLFM-05-075	3"	76.2	85.0	5	15	1.445	30
WLFM-05-100	4"	101.6	112.0	5	15	2.193	30
WLFM-05-125	5"	127.0	137.0	5	15	2.711	30
WLFM-05-150	6"	152.0	162.0	5	15	3.061	30
WLFM-05-200	8"	203.2	214.0	5	15	4.012	30
WLFM-05-250	10"	254.0	226.0	5	15	5.339	12
WLFM-05-300	12"	304.8	319.0	5	15	6.562	12

### APPLICATION

Lightweight and layflat softwall hose, used for the discharge of industrial waste waters in submerged pumps and mobile irrigation systems usage.

### CONSTRUCTION

**Tube:** Black color of NR blend compound.

**Cover:** Black color of NR blend compound. Abrasion and weather resistant.

**Reinforcement:** Multiple layer of high tensile synthetic cord.

**Temperature:** -20°C to +80°C

**Safety Factor:** 3:1