

## STEAM HOSE 18 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
01-PER-STM-18-009	3/8"	10.0	19.5	18	180	0.421	60
01-PER-STM-18-013	1/2"	12.5	23.0	18	180	0.589	60
01-PER-STM-18-019	3/4"	19.0	30.0	18	180	0.846	60
01-PER-STM-18-025	1"	25.4	36.8	18	180	1.095	60
01-PER-STM-18-032	1-1/4"	31.5	43.5	18	180	1.505	30
01-PER-STM-18-038	1-1/2"	38.0	49.5	18	180	1.780	30
01-PER-STM-18-050	2"	51.0	64.0	18	180	2.261	30
01-PER-STM-18-065	2-1/2"	63.0	83.0	18	180	4.214	30
01-PER-STM-18-075	3"	76.0	98.0	18	180	4.962	30

### APPLICATION

Saturated steam hardwall with steel aid reinforced for saturated steam pressure up to 18 bar working pressure, commonly been used in chemical, petrochemical, food and animals farm industries used for cleaning purposes, etc (unable to be used in steam cleaning).

### CONSTRUCTION

**Tube:** Black color of EPDM rubber compound. Resistant to high temperature steam.

**Cover:** Red color of EPDM rubber compound. Resistant to heat and weather.

**Reinforcement:** Double steel wire braided.

**Temperature:** Continuous steam up to +210°C

**Safety Factor:** 10:1