

## FUEL HOSE METRIC SIZE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
<b>RFD-10-M04</b>	3/16"	4.0	10.0	10	30	0.109	100
<b>RFD-10-M05</b>	3/16"	5.0	11.0	10	30	0.124	100
<b>RFD-10-M06</b>	1/4"	6.0	12.0	10	30	0.140	100
<b>RFD-10-M07</b>	1/4"	7.0	13.0	10	30	0.155	100
<b>RFD-10-M08</b>	5/16"	8.0	14.0	10	30	0.172	100
<b>RFD-10-M09</b>	3/8"	9.0	15.0	10	30	0.188	100
<b>RFD-10-M10</b>	3/8"	10.0	16.0	10	30	0.203	100
<b>RFD-10-M11</b>	7/16"	11.0	17.0	10	30	0.219	100
<b>RFD-10-M12</b>	1/2"	12.0	19.0	10	30	0.281	100
<b>RFD-10-M13</b>	1/2"	13.0	20.0	10	30	0.299	100
<b>RFD-10-M14</b>	9/16"	14.0	21.0	10	30	0.317	100
<b>RFD-10-M16</b>	5/8"	16.0	24.0	10	30	0.412	100

### APPLICATION

Softwall hose used in fuel line systems for the transfer of petroleum products under low pressure.

### CONSTRUCTION

**Tube:** Black color of NBR compound. Gasoline and diesel resistance

**Cover:** Black color of NBR compound. Fuel, abrasion and weather resistance.

**Reinforcement:** High tensile synthetic yarn.

**Temperature:** -20°C to +80°C

**Safety Factor:** 3:1