

PUSH ON FUEL HOSE 23 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RPL-23-006	1/4"	6.4	12.7	23	70	0.156	100
RPL-23-008	5/16"	8.0	14.3	23	70	0.184	100
RPL-23-010	3/8"	9.5	15.8	23	70	0.211	100
RPL-23-013	1/2"	12.7	19.6	23	70	0.294	100
RPL-23-016	5/8"	16.0	23.6	23	70	0.394	100
RPL-23-019	3/4"	19.0	28.3	23	70	0.579	100
RPL-23-025	1"	25.4	33.9	23	70	0.675	100

APPLICATION

Softwall hose for low pressure lines, return lines, and drain lines. Used in fuel system or in the crankcase of internal combustion engines in mobile (truck, bus, off highways vehicles), stationary and marine applications.

CONSTRUCTION

Tube: Black color of NBR blend compound. Oil and fuel resistance

Cover: Blue color of EPDM blend compound. Abrasion and weather resistant. Oil mist resistance.

Reinforcement: High tensile synthetic yarn.

Temperature: -40°C to +100°C

Safety Factor: 3:1