

FATTY FOOD SUCTION HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RGS-013	1/2"	12.7	24.0	10	30	0.456	30
RGS-019	3/4"	19.0	31.0	10	30	0.659	30
RGS-025	1"	25.4	37.0	10	30	0.793	30
RGS-032	1-1/4"	31.8	44.0	10	30	1.010	30
RGS-038	1-1/2"	38.1	51.0	10	30	1.256	30
RGS-050	2"	50.8	64.0	10	30	1.744	30
RGS-065	2-1/2"	63.5	77.0	10	30	2.063	30
RGS-075	3"	76.2	90.0	10	30	2.523	30
RGS-100	4"	101.6	118.0	10	30	3.824	30
RGS-150	6"	152.0	170.0	10	30	6.353	30

APPLICATION

Hardwall hose for suction of food products, particularly suitable for oil and fatty foods.

CONSTRUCTION

Tube: White color of food grade NBR blend compound. Cream and alcohol resistance.

Cover: Blue color of food grade NBR blend compound. Abrasion and ozone resistance.

Reinforcement: Multiple layers of high tensile synthetic cord and supported with helix wire.

Temperature: -20°C to +80°C

Sanification : max 150°C for a few minutes with steam; max 60°C for a few minutes with 2% nitric acid, 2% peracetic acid, 2% phosphoric acid, 5% caustic soda

Safety Factor: 3:1