

RADIATOR HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RRRM-025	1"	25.4	35.0	10	30	0.517	1
RRRM-028	1-1/8"	28.6	38.0	10	30	0.555	1
RRRM-032	1-1/4"	31.8	42.0	10	30	0.684	1
RRRM-035	1-3/8"	35.0	45.0	10	30	0.723	1
RRRM-038	1-1/2"	38.1	48.0	10	30	0.768	1
RRRM-041	1-5/8"	41.3	51.0	10	30	0.803	1
RRRM-045	1-3/4"	44.5	55.0	10	30	0.958	1
RRRM-048	1-7/8"	47.8	58.0	10	30	0.982	1
RRRM-050	2"	50.8	62.0	10	30	1.098	1
RRRM-054	2-1/8"	54.0	65.0	10	30	1.132	1
RRRM-057	2-1/4"	57.0	69.0	10	30	1.354	1
RRRM-060	2-3/8"	60.5	72.0	10	30	1.342	1
RRRM-065	2-1/2"	63.5	75.5	10	30	1.494	1
RRRM-067	2-5/8"	66.0	78.0	10	30	1.548	1
RRRM-070	2-3/4"	70.0	82.0	10	30	1.634	1
RRRM-073	2-7/8"	73.3	85.0	10	30	1.643	1
RRRM-075	3"	76.2	88.0	10	30	1.725	1
RRRM-090	3-1/2"	89.0	102.0	10	30	1.861	1
RRRM-100	4"	102.0	114.0	10	30	1.854	1
RRRM-115	4-1/2"	115.0	128.0	10	30	2.727	1
RRRM-125	5"	127.0	140.0	10	30	2.997	1

APPLICATION

Hardwall hose are made to withstand heat, vibration, pressure and cooling systems chemical to provide the flexible connection for coolant flow between the engine and the radiator.

CONSTRUCTION

Tube: Black color of EPDM blend compound. Heat resistance.

Cover: Black color of EPDM blend compound. Heat, abrasion and weather resistance.

Reinforcement: Multiple layers of high tensile synthetic cord.

Temperature: -30°C to 120°C

Safety Factor: 3:1