

OIL DISCHARGE HOSE 10 BAR



| Code | Nominal inch | I.D (mm) | O.D (mm) | Pressure (bar) | | Weight (Kg/m) | Length (m) |
|------------|--------------|----------|----------|----------------|-------|---------------|------------|
| | | | | Working | Burst | | |
| ROD-10-019 | 3/4" | 19.0 | 28.0 | 10 | 30 | 0.405 | 30 |
| ROD-10-025 | 1" | 25.4 | 35.0 | 10 | 30 | 0.568 | 30 |
| ROD-10-032 | 1-1/4" | 31.8 | 42.0 | 10 | 30 | 0.750 | 30 |
| ROD-10-038 | 1-1/2" | 38.1 | 48.0 | 10 | 30 | 0.843 | 30 |
| ROD-10-050 | 2" | 50.8 | 63.0 | 10 | 30 | 1.364 | 30 |
| ROD-10-065 | 2-1/2" | 63.5 | 75.5 | 10 | 30 | 1.367 | 30 |
| ROD-10-075 | 3" | 76.2 | 89.0 | 10 | 30 | 1.795 | 30 |
| ROD-10-089 | 3-1/2" | 88.9 | 102.0 | 10 | 30 | 2.050 | 30 |
| ROD-10-100 | 4" | 101.6 | 115.0 | 10 | 30 | 2.299 | 30 |
| ROD-10-125 | 5" | 127.0 | 141.0 | 10 | 30 | 2.639 | 30 |
| ROD-10-150 | 6" | 152.0 | 166.0 | 10 | 30 | 3.134 | 30 |
| ROD-10-200 | 8" | 203.2 | 219.0 | 10 | 30 | 4.059 | 12 |
| ROD-10-250 | 10" | 254.0 | 272.0 | 10 | 30 | 7.006 | 12 |
| ROD-10-300 | 12" | 304.0 | 323.0 | 10 | 30 | 9.141 | 12 |

APPLICATION

Softwall hose used for transfer of oil and petroleum based products.

CONSTRUCTION

Tube: Black color of NBR blend compound. Oil resistance.

Cover: Black color of NBR blend compound. Oil, abrasion and weather resistance.

Reinforcement: Multiple layer of high tensile synthetic cord.

Temperature: -20°C to +90°C

Safety Factor: 3:1