

WATER DISCHARGE HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RWD-10-013	1/2"	12.7	21.0	10	30	0.272	30
RWD-10-019	3/4"	19.0	29.0	10	30	0.491	30
RWD-10-025	1"	25.4	35.0	10	30	0.588	30
RWD-10-032	1-1/4"	31.8	42.0	10	30	0.776	30
RWD-10-038	1-1/2"	38.1	48.0	10	30	0.872	30
RWD-10-050	2"	50.8	62.0	10	30	1.300	30
RWD-10-065	2-1/2"	63.5	76.0	10	30	1.519	30
RWD-10-075	3"	76.2	89.0	10	30	1.861	30
RWD-10-100	4"	101.6	115.0	10	30	2.495	30
RWD-10-125	5"	127.0	141.0	10	30	3.567	30
RWD-10-150	6"	152.0	166.0	10	30	4.234	30
RWD-10-200	8"	203.2	219.0	10	30	5.288	12
RWD-10-250	10"	254.0	272.0	10	30	7.256	12
RWD-10-300	12"	304.0	323.0	10	30	9.466	12

APPLICATION

Softwall discharge hose used in water transfer, non-corrosive liquids, used in construction site, industries and agriculture.

CONSTRUCTION

Tube: Black color of NR blend compound.

Cover: Black color of NR blend compound. Abrasion and weather resistant.

Reinforcement: Multiple layers of high tensile synthetic cord.

Temperature: -20°C to +80°C

Safety Factor: 3:1