

YELLOW AIR HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
YAH-20-006	1/4"	6.4	13.0	20	60	0.174	100
YAH-20-008	5/16"	7.9	15.0	20	60	0.223	100
YAH-20-010	3/8"	9.5	17.0	20	60	0.274	100
YAH-20-013	1/2"	12.7	21.0	20	60	0.384	100
YAH-20-016	5/8"	15.9	25.0	20	60	0.508	100
YAH-20-019	3/4"	19.0	29.0	20	60	0.661	100
YAH-20-022	7/8"	22.2	33.0	20	60	0.820	100
YAH-20-025	1"	25.4	36.0	20	60	0.903	100

APPLICATION

Softwall hose ideal for heavy duty compressed air with light traces of oil mist, for civil engineering in road constructions, quarries and mines. Also for general industries usage.

CONSTRUCTION

Tube: Black color of SBR blend compound. Oil mist resistance.

Cover: Yellow color of EPDM blend compound. Abrasion and weather resistance.

Reinforcement: High tensile synthetic yarn.

Temperature: -20°C to +80°C

Safety Factor: 3:1