

WATER DISCHARGE HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RWDM-20-013	1/2"	12.7	21.0	20	60	0.277	30
RWDM-20-019	3/4"	19.0	29.0	20	60	0.500	30
RWDM-20-025	1"	25.4	35.0	20	60	0.566	30
RWDM-20-032	1-1/4"	31.8	45.0	20	60	0.919	30
RWDM-20-038	1-1/2"	38.1	51.0	20	60	1.033	30
RWDM-20-050	2"	50.8	65.0	20	60	1.421	30
RWDM-20-065	2-1/2"	63.5	78.0	20	60	1.680	30
RWDM-20-075	3"	76.2	92.0	20	60	2.146	30
RWDM-20-100	4"	101.6	118.0	20	60	2.982	30
RWDM-20-125	5"	127.0	143.0	20	60	3.105	30
RWDM-20-150	6"	152.0	170.0	20	60	3.700	30
RWDM-20-200	8"	203.2	222.0	20	60	4.782	12
RWDM-20-250	10"	254.0	278.0	20	60	7.086	12
RWDM-20-300	12"	304.0	330.0	20	60	9.608	12

APPLICATION

Softwall discharge hose used in water transfer, non-corrosive liquids, used in construction site, industries and agriculture.

CONSTRUCTION

Tube: Black color of NR blend compound.

Cover: Black color of NR blend compound. Abrasion and weather resistant.

Reinforcement: Multiple layer of high tensile synthetic cord.

Temperature: -20°C to +80°C

Safety Factor: 3:1