

CORR WATER SUCTION HOSE WITH CUFF END 5 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RWS-05-050/3M	2"	50.8	62.0	5	15	1.755	3.0
RWS-05-050/4.5M	2"	50.8	62.0	5	15	1.755	4.5
RWS-05-050/6M	2"	50.8	62.0	5	15	1.755	6.0
RWS-05-050/7.5M	2"	50.8	62.0	5	15	1.755	7.5
RWS-05-075/3M	3"	76.2	87.0	5	15	2.556	3.0
RWS-05-075/4.5M	3"	76.2	87.0	5	15	2.556	4.5
RWS-05-075/6M	3"	76.2	87.0	5	15	2.556	6.0
RWS-05-075/7.5M	3"	76.2	87.0	5	15	2.556	7.5
RWS-05-100/3M	4"	101.6	114.0	5	15	3.993	3.0
RWS-05-100/4.5M	4"	101.6	114.0	5	15	3.993	4.5
RWS-05-100/6M	4"	101.6	114.0	5	15	3.993	6.0
RWS-05-100/7.5M	4"	101.6	114.0	5	15	3.993	7.5
RWS-05-125/4.5M	5"	127.0	140.0	5	15	5.235	4.5
RWS-05-125/6M	5"	127.0	140.0	5	15	5.235	6.0
RWS-05-125/7.5M	5"	127.0	140.0	5	15	5.235	7.5
RWS-05-150/4.5M	6"	152.0	166.0	5	15	7.150	4.5
RWS-05-150/6M	6"	152.0	166.0	5	15	7.150	6.0
RWS-05-150/7.5M	6"	152.0	166.0	5	15	7.150	7.5
RWS-05-200/4.5M	8"	203.2	220.0	5	15	10.976	4.5
RWS-05-200/6M	8"	203.2	220.0	5	15	10.976	6.0
RWS-05-200/7.5M	8"	203.2	220.0	5	15	10.976	7.5
RWS-05-250/4.5M	10"	254.0	270.0	5	15	14.438	4.5
RWS-05-250/6M	10"	254.0	270.0	5	15	14.438	6.0
RWS-05-250/7.5M	10"	254.0	270.0	5	15	14.438	7.5
RWS-05-300/4.5M	12"	304.8	323.0	5	15	16.506	4.5
RWS-05-300/6M	12"	304.8	323.0	5	15	16.506	6.0
RWS-05-300/7.5M	12"	304.8	323.0	5	15	16.506	7.5



PERAFLEX®



APPLICATION

Rubber suction hose used for the transfer of fluid water in water slurry medium in negative pressure applications. 6 or 7.5 meter lengths for ease to handle and good bend radius.

CONSTRUCTION

Tube: Black color of NR blend compound.

Cover: Black color of NR blend compound. Abrasion and weather resistant.

Reinforcement: Multiple layer of high tensile synthetic cord and supported with helix wire.

Temperature: -20°C to +80°C

Safety Factor: 3:1