

SLURRY DISCHARGE HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
SLDM-10-038	1-1/2"	38.1	52.0	10	30	1.087	30
SLDM-10-050	2"	50.8	67.0	10	30	1.682	30
SLDM-10-065	2-1/2"	63.5	83.0	10	30	2.286	30
SLDM-10-075	3"	76.2	96.0	10	30	2.760	30
SLDM-10-100	4"	101.6	123.0	10	30	3.847	30
SLDM-10-125	5"	127.0	149.0	10	30	4.724	30
SLDM-10-150	6"	152.0	174.0	10	30	5.308	30
SLDM-10-200	8"	203.2	226.0	10	30	7.107	12

APPLICATION

For discharge of abrasive slurries in mines and quarries, dry material handling of sand, gravel, grain, cement, slag and other such materials. Suitable for mud-removing pipeline-joining as the kit of the mire-digging ship in dredging the bay, river, lake etc.

CONSTRUCTION

Tube: Black color of NR blend compound. Oily mud resistance.

Cover: Black color of SBR blend compound. Sea water resistant, abrasion and weather resistant.

Reinforcement: Multiple layers of high tensile synthetic cord.

Temperature: -20°C to +80°C

Safety Factor: 3:1