

## YELLOW AIR HOSE 40 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
YAHM-40-013	1/2"	13.1	20.0	40	120	0.365	60
YAHM-40-019	3/4"	19.3	29.0	40	120	0.520	60
YAHM-40-025	1"	25.9	35.5	40	120	0.821	60
YAHM-40-032	1-1/4"	32.4	42.0	40	120	1.114	30
YAHM-40-038	1-1/2"	38.7	51.7	40	120	1.529	30
YAHM-40-050	2"	51.3	63.0	40	120	2.058	30
YAHM-40-065	2-1/2"	63.5	80.0	40	120	4.196	30
YAHM-40-075	3"	76.2	95.0	40	120	5.394	30
YAHM-40-100	4"	101.6	118.5	40	120	6.110	30

### APPLICATION

High pressure steel wire reinforced compressed air with light traces & oil mist for civil engineering in road constructions, quarries and mines, also for general industries usage.

### CONSTRUCTION

**Tube:** Black color of synthetic rubber compound. Resistant to air.

**Cover:** Yellow color of synthetic rubber compound. Abrasion and weather resistance.

**Reinforcement:** Single steel wire braided.

**Temperature:** -40°C to +90°C

**Safety Factor:** 3:1