

## WATER SUCTION HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RWSM-20-013	1/2"	12.7	22.0	20	60	0.405	30
RWSM-20-019	3/4"	19.0	29.0	20	60	0.569	30
RWSM-20-025	1"	25.4	36.0	20	60	0.808	30
RWSM-20-032	1-1/4"	31.8	43.0	20	60	1.004	30
RWSM-20-038	1-1/2"	38.1	49.0	20	60	1.136	30
RWSM-20-050	2"	50.8	65.0	20	60	1.993	30
RWSM-20-065	2-1/2"	63.5	79.0	20	60	2.642	30
RWSM-20-075	3"	76.2	93.0	20	60	3.321	30
RWSM-20-090	3-1/2"	88.9	106.0	20	60	3.854	30
RWSM-20-100	4"	101.6	119.0	20	60	4.772	30
RWSM-20-125	5"	127.0	146.0	20	60	5.746	30
RWSM-20-150	6"	152.0	173.0	20	60	7.803	30
RWSM-20-200	8"	203.2	231.0	20	60	13.142	12
RWSM-20-250	10"	254.0	284.0	20	60	19.013	12
RWSM-20-300	12"	304.0	335.0	20	60	24.615	12
RWSM-20-350	14"	355.6	396.0	20	60	33.932	12
RWSM-20-406	16"	406.0	450.0	20	60	41.889	12

### APPLICATION

Hardwall hose for suction of water and non-corrosive fluids. Suitable for agricultural, industrial and other applications.

### CONSTRUCTION

**Tube:** Black color of SBR blend compound.

**Cover:** Black color of NR blend compound. Abrasion and weather resistance.

**Reinforcement:** Multiple layers of high tensile synthetic cord and supported with helix wire.

**Temperature:** -20°C to +80°C

**Safety Factor:** 3:1