

TOYOSPRING HOSE



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)	Weight (kg/reel)	Length (m)	Minimum Bending Radius (mm)
				Working			
TS-6	1/4	6	11	-1 to 8	11	100	25
TS-8	5/16	8	13.5	-1 to 8	14	100	35
TS-9	3/8	9	15	-1 to 8	17	100	40
TS-12	1/2	12	18	-1 to 5	23	100	50
TS-15	5/8	15	22	-1 to 5	32	100	60
TS-19	3/4	19	26	-1 to 4	21	50	80
TS-25	1	25	33	-1 to 4	27	50	100
TS-32	1-1/4	32	41	-1 to 3	31	40	130
TS-38	1-1/2	38	48	-1 to 3	39	40	150
TS-45	1-3/4	45	56	-1 to 3	55	40	189
TS-50	2	50	62	-1 to 3	60	40	200
TS-63	2-1/2	63	80	-1 to 2	54	20	265
TS-75	3	75	92	-1 to 2	62	20	310
TS-90	3-1/2	90	108	-1 to 2	44	10	370
TS-100	4	100	118	-1 to 2	48	10	410



APPLICATION

For general piping and oil resistant. Excellent oil resistance performance and prevents hardening of the hose, providing a long service life. Highly transparent and provides security in fluid verification. Safe and secure due to its compliance with corrected RoHS2 regulations.

CONSTRUCTION

Cover: Natural transparent with image line

Main Material: Soft PVC

Reinforcement: Hard steel wire

Temperature: Range -5°C - 60°C