

TOYOGOMA®

Quality Hoses, Trusted Excellence.

PVC SPRING SUCTION HOSE (ANTI-STATIC)

SPECIFICATIONS

- Designed for safe transfer of oils, fuels, gases, and powders in static-prone environments such as factories, mines, and oil storage facilities. Built with anti-static properties and copper wire to prevent static build-up and ensure user safety.
- Offers good flexibility, small bending radius, UV resistance, and long service life.
- Temperature range: -5°C to +65°C.

CONSTRUCTION

The Toyogoma hose is constructed from durable PVC with embedded copper wire and high-tensile steel wire reinforcement for strength and electrostatic protection. The transparent body allows easy visual monitoring.

Additionally, Toyogoma hoses can be customized upon request to suit various industrial needs. Custom options include different diameters and working pressure ratings, ensuring the hose performs optimally in diverse applications across industries.

INCH	ID (MM)	OD (MM)	Working Pressure (Bar)	Length per roll (m)	Weight kg/roll
1/4	6	11	8	100	12
3/8	9	13.5	8	100	17
1/2	12	18	6	100	18
5/8	15	22	6	100	17
3/4	19	26	6	50	15
1	25	32	6	50	25
1 1/4	32	34	5	50	28
1 1/2	38	47	5	50	40
2	50	61	5	50	50
2 1/2	64	78	4	40	63
3	75	90	4	20	72
3 1/2	90	106	4	20	92
4	100	116	4	20	100
5	127	141	2	20	126
6	152	166	2	20	75
8	200	220	2	10	120