

BULK MATERIAL SUCTION HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
01-PER-RBS-10-038	1-1/2"	38.1	52	10	30	1.389	30
01-PER-RBS-10-050	2"	50.8	67	10	30	2.206	30
01-PER-RBS-10-065	2-1/2"	63.5	84	10	30	3.306	30
01-PER-RBS-10-075	3"	76.2	97	10	30	3.969	30
01-PER-RBS-10-090	3-1/2"	88.9	110	10	30	4.161	30
01-PER-RBS-10-100	4"	101.6	124	10	30	5.721	30
01-PER-RBS-10-125	5"	127	150	10	30	6.827	30
01-PER-RBS-10-150	6"	152	176	10	30	8.701	30
01-PER-RBS-10-200	8"	203.2	230	10	30	13.281	30
01-PER-RBS-10-250	10"	254	284	10	30	18.165	12
01-PER-RBS-10-300	12"	304.8	336	10	30	24.969	12
01-PER-RBS-10-350	14"	355.6	390	10	30	30.189	12
01-PER-RBS-10-400	16"	406.4	446	10	30	35.454	12

APPLICATION:

FOR SUCTION OF BULK MATERIAL DRY CEMENT, GRAVEL, SAND, ETC. CONSTRUCTION INDUSTRY

CONSTRUCTION:

TUBE: ANTISTATIC BLACK NR BLEND COMPOUND. HIGH ABRASION RESISTANCE.

COVER: BLACK COLOR OF NR BLEND COMPOUND. ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: MULTIPLE LAYERS OF HIGH TENSILE SYNTHETIC CORD AND SUPPORTED WITH HELIX WIRE.

SURFACE TEXTURE: WRAPPED FINISHING.

TEMPERATURE: -20°C TO +80°C

SAFETY FACTOR: 3:1