

CEMENT SUCTION HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RHSM-10-038	1-1/2"	38.1	52	10	30	1.389	30
RHSM-10-050	2"	50.8	67	10	30	2.203	30
RHSM-10-065	2-1/2"	63.5	84	10	30	3.3	30
RHSM-10-075	3"	76.2	97	10	30	3.962	30
RHSM-10-090	3-1/2"	88.9	110	10	30	4.152	30
RHSM-10-100	4"	101.6	124	10	30	5.711	30
RHSM-10-125	5"	127	150	10	30	6.815	30
RHSM-10-150	6"	152	176	10	30	8.687	30
RHSM-10-200	8"	203.2	230	10	30	13.261	30
RHSM-10-250	10"	254	284	10	30	18.141	12
RHSM-10-300	12"	304.8	336	10	30	24.941	12
RHSM-10-350	14"	355.6	390	10	30	30.149	12
RHSM-10-400	16"	406.4	446	10	30	35.409	12

APPLICATION:

HARDWALL HOSE USED FOR SUCTION OF DRY CEMENT, SAND, GRAVEL, FEED, SEEDS ETC.

CONSTRUCTION:

TUBE: ANTISTATIC BLACK SBR BLEND COMPOUND. HIGH ABRASION RESISTANCE.

COVER: BLACK COLOR OF SBR BLEND COMPOUND. ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: MULTIPLE LAYERS OF HIGH TENSILE SYNTHETIC CORD AND SUPPORTED WITH HELIX WIRE.

TEMPERATURE: -20°C TO +80°C

SAFETY FACTOR: 3:1