

COMPRESSED AIR (BULL) HOSE 40 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
YAHM-40-013	1/2"	13.1	20	40	120	0.365	60
YAHM-40-019	3/4"	19.3	29	40	120	0.52	60
YAHM-40-025	1"	25.9	35.5	40	120	0.821	60
YAHM-40-032	1-1/4"	32.4	42	40	120	1.114	30
YAHM-40-038	1-1/2"	38.7	51.7	40	120	1.529	30
YAHM-40-050	2"	51.3	63	40	120	2.058	30
YAHM-40-065	2-1/2"	63.5	80	40	120	4.196	30
YAHM-40-075	3"	76.2	95	40	120	5.394	30
YAHM-40-100	4"	101.6	118.5	40	120	6.11	30

APPLICATION:

HIGH PRESSURE STEEL WIRE REINFORCED COMPRESSED AIR WITH LIGHT TRACES & OIL MIST FOR CIVIL ENGINEERING IN ROAD CONSTRUCTIONS, QUARRIES AND MINES, ALSO FOR GENERAL INDUSTRIES USAGE.

CONSTRUCTION:

TUBE: BLACK COLOR OF SYNTHETIC RUBBER COMPOUND. RESISTANT TO AIR.

COVER: YELLOW COLOR OF SYNTHETIC RUBBER COMPOUND. ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: SINGLE STEEL WIRE BRAIDED.

TEMPERATURE: -40°C TO +90°C

SAFETY FACTOR: 3:1