

FUEL INJECTION HOSE 15 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RFI-15-005	3/16"	5	10.5	15	45	0.11	100
RFI-15-006	1/4"	6.3	13	15	45	0.165	100
RFI-15-008	5/16"	7.5	14.6	15	45	0.202	100
RFI-15-010	3/8"	9.5	16	15	45	0.216	100
RFI-15-013	1/2"	12.7	20	15	45	0.309	100
RFI-15-016	5/8"	16	24.5	15	45	0.442	100
RFI-15-019	3/4"	19	28.5	15	45	0.583	100
RFI-15-025	1"	25.4	35	15	45	0.759	100

APPLICATION:
SUITABLE FOR DIESEL AND BIO-DIESEL FUEL.

CONSTRUCTION:
TUBE: BLACK COLOR OF NBR COMPOUND. GASOLINE AND DIESEL RESISTANCE
COVER: BLACK COLOR OF NBR COMPOUND. FUEL, ABRASION AND WEATHER RESISTANCE.
REINFORCEMENT: HIGH TENSILE SYNTHETIC YARN.
TEMPERATURE: -30°C TO +150°C
SAFETY FACTOR: 3:1