

## OFFSHORE OIL S&D BUNKERING HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
ROS-20-OFF-050	2"	50.8	67	20	60	2.255	30
ROS-20-OFF-065	2-1/2"	63.5	82	20	60	3.151	30
ROS-20-OFF-075	3"	76.2	98	20	60	3.985	30
ROS-20-OFF-100	4"	101.6	124	20	60	5.449	30
ROS-20-OFF-125	5"	127	150	20	60	7.024	30
ROS-20-OFF-150	6"	152	178	20	60	8.545	30
ROS-20-OFF-200	8"	203.2	235	20	60	14.655	12
ROS-20-OFF-250	10"	254	290	20	60	21.509	12
ROS-20-OFF-300	12"	304	342	20	60	28.332	12
ROS-20-OFF-400	16"	406	450	20	60	38.539	12

**APPLICATION:**

HARD WALL HOSE, FLEXIBLE, USED FOR HEAVY DUTY SUCTION AND DISCHARGE OF OIL, FUEL AND PETROLEUM FROM TANKERS TO BARGE, BUNKERING SERVICES AND INDUSTRIAL APPLICATION WITH AROMATIC CONTENT UP TO 50%, EXCLUDING OILS WITH ESTHER BASE.

**CONSTRUCTION:**

TUBE: BLACK COLOR OF SPECIAL NBR COMPOUND. FUEL RESISTANCE

COVER: BLACK COLOR OF NBR BLEND COMPOUND. OIL, ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: MULTIPLE LAYERS OF HIGH TENSILE SYNTHETIC CORD AND SUPPORTED WITH HELIX WIRE.

EMBEDDED WITH ANTISTATIC COPPER WIRE.

TEMPERATURE: -20°C TO +100°C

SAFETY FACTOR: 3:1