

OIL DISCHARGE HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
ROD-10-019	3/4"	19	28	10	30	0.405	30
ROD-10-025	1"	25.4	35	10	30	0.568	30
ROD-10-032	1-1/4"	31.8	42	10	30	0.75	30
ROD-10-038	1-1/2"	38.1	48	10	30	0.843	30
ROD-10-050	2"	50.8	63	10	30	1.364	30
ROD-10-065	2-1/2"	63.5	75.5	10	30	1.367	30
ROD-10-075	3"	76.2	89	10	30	1.795	30
ROD-10-089	3-1/2"	88.9	102	10	30	2.05	30
ROD-10-100	4"	101.6	115	10	30	2.299	30
ROD-10-125	5"	127	141	10	30	2.639	30
ROD-10-150	6"	152	166	10	30	3.134	30
ROD-10-200	8"	203.2	219	10	30	4.059	12
ROD-10-250	10"	254	272	10	30	7.006	12
ROD-10-300	12"	304	323	10	30	9.141	12

APPLICATION:
SOFTWALL HOSE USED FOR TRANSFER OF OIL AND PETROLEUM BASED PRODUCTS.

CONSTRUCTION:
TUBE: BLACK COLOR OF NBR BLEND COMPOUND. OIL RESISTANCE.
COVER: BLACK COLOR OF NBR BLEND COMPOUND. OIL, ABRASION AND WEATHER RESISTANCE.
REINFORCEMENT: MULTIPLE LAYER OF HIGH TENSILE SYNTHETIC CORD.
TEMPERATURE: -20°C TO +90°C
SAFETY FACTOR: 3:1