

SLURRY DISCHARGE HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
SLDM-10-038	1-1/2"	38.1	52	10	30	1.087	30
SLDM-10-050	2"	50.8	67	10	30	1.682	30
SLDM-10-065	2-1/2"	63.5	83	10	30	2.286	30
SLDM-10-075	3"	76.2	96	10	30	2.76	30
SLDM-10-100	4"	101.6	123	10	30	3.847	30
SLDM-10-125	5"	127	149	10	30	4.724	30
SLDM-10-150	6"	152	174	10	30	5.308	30
SLDM-10-200	8"	203.2	226	10	30	7.107	12

APPLICATION:

FOR DISCHARGE OF ABRASIVE SLURRIES IN MINES AND QUARRIES, DRY MATERIAL HANDLING OF SAND, GRAVEL, GRAIN, CEMENT, SLAG AND OTHER SUCH MATERIALS. SUITABLE FOR MUD-REMOVING PIPELINE-JOINING AS THE KIT OF THE MIRE-DIGGING SHIP IN DREDGING THE BAY, RIVER, LAKE ETC.

CONSTRUCTION:

TUBE: BLACK COLOR OF NR BLEND COMPOUND. OILY MUD RESISTANCE.

COVER: BLACK COLOR OF SBR BLEND COMPOUND. SEA WATER RESISTANT, ABRASION AND WEATHER RESISTANT.

REINFORCEMENT: MULTIPLE LAYERS OF HIGH TENSILE SYNTHETIC CORD.

TEMPERATURE: -20°C TO +80°C

SAFETY FACTOR: 3:1