

SLURRY SUCTION HOSE 10 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
SLS-10-038	1-1/2"	38.1	52	10	30	1.402	30
SLS-10-050	2"	50.8	67	10	30	2.23	30
SLS-10-065	2-1/2"	63.5	84	10	30	3.336	30
SLS-10-075	3"	76.2	97	10	30	4.009	30
SLS-10-090	3-1/2"	88.9	110	10	30	4.2	30
SLS-10-100	4"	101.6	124	10	30	5.784	30
SLS-10-125	5"	127	150	10	30	6.908	30
SLS-10-150	6"	152	176	10	30	8.702	30
SLS-10-200	8"	203.2	230	10	30	13.281	30
SLS-10-250	10"	254	284	10	30	18.166	12
SLS-10-300	12"	304.8	335	10	30	24.071	12
SLS-10-350	14"	355.6	388	10	30	28.42	12
SLS-10-400	16"	406.4	444	10	30	33.44	12



SLURRY SUCTION HOSE 10 BAR

APPLICATION:

FOR SUCTION OF ABRASIVE SLURRIES IN MINES AND QUARRIES, DRY MATERIAL HANDLING OF SAND, GRAVEL, GRAIN, CEMENT, SLAG AND OTHER SUCH MATERIALS. SUITABLE FOR MUD-REMOVING PIPELINE-JOINING AS THE KIT OF THE MIRE-DIGGING SHIP IN DREDGING THE BAY, RIVER, LAKE ETC.

CONSTRUCTION:

TUBE: BLACK COLOR OF NR BLEND COMPOUND. OILY MUD RESISTANCE.

COVER: BLACK COLOR OF SBR BLEND COMPOUND. SEA WATER RESISTANT, ABRASION AND WEATHER RESISTANT.

REINFORCEMENT: MULTIPLE LAYER OF HIGH TENSILE SYNTHETIC CORD AND SUPPORTED WITH HELIX WIRE.

TEMPERATURE: -20°C TO +80°C

SAFETY FACTOR: 3:1