

YELLOW AIR HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
YAH-20-006	1/4"	6.4	13	20	60	0.174	100
YAH-20-008	5/16"	7.9	15	20	60	0.223	100
YAH-20-010	3/8"	9.5	17	20	60	0.274	100
YAH-20-013	1/2"	12.7	21	20	60	0.384	100
YAH-20-016	5/8"	15.9	25	20	60	0.508	100
YAH-20-019	3/4"	19	29	20	60	0.661	100
YAH-20-022	7/8"	22.2	33	20	60	0.82	100
YAH-20-025	1"	25.4	36	20	60	0.903	100
YAHM-20-032	1-1/4"	31.8	46	20	60	1.142	30
YAHM-20-038	1-1/2"	38.1	52	20	60	1.295	30
YAHM-20-050	2"	50.8	65	20	60	1.617	30
YAHM-20-065	2-1/2"	63.5	80	20	60	2.061	30
YAHM-20-075	3"	76.2	94	20	60	2.64	30
YAHM-20-100	4"	101.6	120	20	60	2.911	30



Peraflex



YELLOW AIR HOSE 20 BAR

APPLICATION:

HOSE IDEAL FOR HEAVY DUTY AIR WITH LIGHT TRACES OF OIL MIST, FOR CIVIL ENGINEERING IN ROAD CONSTRUCTIONS, QUARRIES AND MINES. ALSO FOR GENERAL INDUSTRIES USAGE.

CONSTRUCTION:

TUBE: BLACK COLOR OF SBR BLEND COMPOUND. OIL MIST RESISTANCE.

COVER: YELLOW COLOR OF EPDM BLEND COMPOUND. ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: HIGH TENSILE SYNTHETIC YARN.

TEMPERATURE: -20°C TO +85°C

SAFETY FACTOR: 3:1

*YAH – EXTRUSION HOSE

*YAHM – MANDREL BUILD HOSE