

TOYOX ROCK-Y HOSE (FOR AIR)



ROCK-Y HOSE For Air

Application	Factory equipment air hoses, engineering works compressor air hoses (including for breakers, air chippers, and coal picks)					
Fluid	 Water (industrial use)  Air					
Function	Positive pressure (pressure feed)	■■■■	Transparent	■■■■	Chemical-resistant	■■■■
	Negative pressure (vacuum)	■■■■	Flexible	■■■■	Low odor	■■■■
	High-pressure-resistant	■■■■	Kinking/collapse prevention	■■■■	Low elution	■■■■
	Heat-resistant	■■■■	Oil-resistant (animal/vegetable oil)	■■■■	Non-adhesive	■■■■
	Cold-resistant	■■■■	Oil-resistant (mineral oil)	■■■■	Antistatic	■■■■
Regulatory	RoHS 2 compliant					
Specification	Main material	Soft PVC				
	Reinforcing material	Polyester thread				
	Inner diameter	9.5mm~32mm				
	Operating temperature range	-5°C~60°C				
	Other					

Specifications table by size Operating temperature range -5°C ~ 60°C

Model	Inner diameter × Outer diameter (mm)	Operating pressure (MPa)	Standard weight (kg/roll)	Standard length (m)	Minimum bending radius (mm)
RY-9	9.5 × 16.0	0~1.7	18	100	50
RY-12	12.5 × 20.0	0~1.7	27	100	60
RY-19	19.0 × 27.0	0~1.5	41	100	100
RY-25	25.0 × 33.0	0~1.2	51	100	150
RY-32	32.0 × 43.0	0~1.0	45	50	210

Packing: film packing

Coloring: yellow