

TOYOX TOYOFOODS HOSE (FOR FOOD / OIL RESISTANT)



TOYOFOODS HOSE Food / oil resistant

Application		For delivering foods, beverages, water and more							
Fluid		 Air  Mineral oil  Animal/vegetable oil  Heat-resistant  Food and beverage  Chemicals and cosmetics  Powders							
Function		Positive pressure (pressure feed)		Transparent		Chemical-resistant		Dew condensation prevention	
		Negative pressure (vacuum)		Flexible		Low odor		Abrasion-resistant	
		High-pressure-resistant		Kinking/collapse prevention		Low elution		Flame retardant	
		Heat-resistant		Oil-resistant (animal/vegetable oil)		Non-adhesive		Plasticizer-free	
		Cold-resistant		Oil-resistant (mineral oil)		Antistatic		Disposal sorting not required	
Regulatory		Food Sanitation Act No. 370 compliant FDA compliant BPOM compliant RoHS 2 compliant							
Specification	Main material	Soft PVC							
	Reinforcing material	Polyester thread							
	Inner diameter	6mm~50mm							
	Operating temperature range	-5°C~70°C							
	Other								



TOYOX TOYOFOODS HOSE (FOR FOOD / OIL RESISTANT)

Specifications table by size Operating temperature range -5°C ~ 70°C

Model	Inner diameter × Outer diameter (mm)	Operating pressure (MPa)	Standard weight (kg/roll)	Standard length (m)	Minimum bending radius (mm)
TFB-6	6 × 11	0~1.0	9	100	30
TFB-8	8 × 13.5	0~1.0	13	100	40
TFB-9	9 × 15	0~1.0	15	100	45
TFB-10	10 × 16	0~1.0	16	100	50
TFB-12	12 × 18	0~0.8	19	100	65
TFB-15	15 × 22	0~0.8	27	100	95
TFB-19	19 × 26	0~0.6	16	50	120
TFB-25	25 × 33	0~0.6	25	50	165
TFB-32	32 × 41	0~0.4	35	50	200
TFB-38	38 × 48	0~0.4	45	50	300
TFB-50	50 × 62	0~0.3	54	40	440

Packing: bobbin style (TFB-6 to 25) / film packing (TFB-32 to 50)

Coloring: natural clear, green line added