

TOYOX TOYOSPRAY HOSE (FOR AIR)



TOYOSPRAY HOSE For Air

Application	For factory equipment hoses and air tools such as impact wrenches, air screwdrivers and spray guns					
Fluid	 Water (Industrial use)  Air					
Function	Positive pressure (pressure feed)	■■■■	Transparent	■■■■	Chemical-resistant	■■■■
	Negative pressure (vacuum)	■■■■	Flexible	■■■■	Low odor	■■■■
	High-pressure-resistant	■■■■	Kinking/collapse prevention	■■■■	Low elution	■■■■
	Heat-resistant	■■■■	Oil-resistant (animal/vegetable oil)	■■■■	Non-adhesive	■■■■
	Cold-resistant	■■■■	Oil-resistant (mineral oil)	■■■■	Antistatic	■■■■
Regulatory	RoHS 2 compliant					
Specification	Main material	Soft PVC				
	Reinforcing material	Polyester thread				
	Inner diameter	8.5mm				
	Operating temperature range	~60°C				
	Other					

Specifications table by size Operating temperature range ~ 60°C

Model	Inner diameter × Outer diameter (mm)	Operating pressure (MPa)	Standard weight (kg/roll)	Standard length (m)	Minimum bending radius (mm)
SP-8	8.5 × 14	0~4.0	15	100	50

Packing: Bobbin style Coloring: Yellow