

OIL SUCTION / DELIVERY HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
ROSM-20-013	1/2"	12.7	22	20	60	0.39	30
ROSM-20-019	3/4"	19	29	20	60	0.58	30
ROSM-20-025	1"	25.4	38	20	60	0.969	30
ROSM-20-032	1-1/4"	31.8	44	20	60	1.08	30
ROSM-20-038	1-1/2"	38.1	52	20	60	1.473	30
ROSM-20-050	2"	50.8	65	20	60	1.933	30
ROSM-20-065	2-1/2"	63.5	79	20	60	2.565	30
ROSM-20-075	3"	76.2	92	20	60	3	30
ROSM-20-100	4"	101.6	120	20	60	4.931	30
ROSM-20-125	5"	127	146	20	60	5.594	30
ROSM-20-150	6"	152	174	20	60	7.584	30
ROSM-20-200	8"	203.2	228	20	60	10.541	12
ROSM-20-250	10"	254	284	20	60	17.263	12
ROSM-20-300	12"	304	335	20	60	22.49	12
ROSM-20-350	14"	355.6	396	20	60	30.911	12
ROSM-20-400	16"	406	450	20	60	37.907	12



Peraflex



OIL SUCTION / DELIVERY HOSE 20 BAR

APPLICATION:

HARDWALL HOSE USED FOR THE SUCTION OF OIL AND PETROLEUM BASED PRODUCTS.

CONSTRUCTION:

TUBE: BLACK COLOR OF NBR BLEND COMPOUND. OIL RESISTANCE.

COVER: BLACK COLOR OF NBR BLEND COMPOUND. OIL, ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: MULTIPLE LAYERS OF HIGH TENSILE SYNTHETIC CORD AND SUPPORTED WITH HELIX WIRE. EMBEDDED WITH ANTISTATIC COPPER WIRE.

TEMPERATURE: -20°C TO +90°C

SAFETY FACTOR: 3:1

INDUSTRIAL RUBBER HOSE