

TANK TRUCK HOSE 5 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
ROTS-05-025	1"	25.4	35	5	15	0.7	30
ROTS-05-032	1-1/4"	31.8	43	5	15	1.012	30
ROTS-05-038	1-1/2"	38.1	49	5	15	1.146	30
ROTS-05-050	2"	50.8	63	5	15	1.763	30
ROTS-05-065	2-1/2"	63.5	75	5	15	1.984	30
ROTS-05-075	3"	76.2	88	5	15	2.446	30
ROTS-05-100	4"	101.6	114	5	15	3.636	30

APPLICATION:

HARDWALL HOSE DESIGNED FOR TANK TRUCK TRANSFER OF PETROLEUM PRODUCTS WITH AROMATIC CONTENT UP TO 50%.

CONSTRUCTION:

TUBE: BLACK COLOR OF NBR BLEND COMPOUND. OIL RESISTANCE.

COVER: BLACK COLOR OF NBR BLEND COMPOUND. OIL, ABRASION, AND WEATHER RESISTANCE.

REINFORCEMENT: MULTIPLE LAYERS OF HIGH TENSILE SYNTHETIC CORD AND SUPPORTED WITH HELIX WIRE. EMBEDDED ANTISTATIC COPPER WIRE.

TEMPERATURE: -20°C TO +90°C

SAFETY FACTOR: 3:1