

MULTIPURPOSE HOSE 20 BAR



Code	Nominal inch	I.D (mm)	O.D (mm)	Pressure (bar)		Weight (Kg/m)	Length (m)
				Working	Burst		
RMP-20-006	1/4"	6.4	14	20	60	0.211	100
RMP-20-008	5/16"	8	15	20	60	0.222	100
RMP-20-010	3/8"	9.5	17	20	60	0.276	100
RMP-20-013	1/2"	12.7	21	20	60	0.385	100
RMP-20-016	5/8"	16	25	20	60	0.506	100
RMP-20-019	3/4"	19	29	20	60	0.664	100
RMP-20-022	7/8"	22	32	20	60	0.749	100
RMP-20-025	1"	25.4	36	20	60	0.907	100
RMPM-20-025	1"	25.4	37	20	60	0.708	30
RMPM-20-032	1-1/4"	31.8	45	20	60	1.032	30
RMPM-20-038	1-1/2"	38.1	52	20	60	1.297	30
RMPM-20-050	2"	50.8	66	20	60	1.786	30
RMPM-20-065	2-1/2"	63.5	81	20	60	2.304	30
RMPM-20-075	3"	76.2	94	20	60	2.649	30
RMPM-20-100	4"	101.6	120	20	60	3.452	30



Peraflex



MULTIPURPOSE HOSE 20 BAR

APPLICATION:

HIGH QUALITY MULTIPURPOSE HOSE SUITABLE FOR AIR, WATER

CONSTRUCTION:

TUBE: BLACK COLOR OF NBR BLEND COMPOUND. OIL AND NON-AGGRESSIVE CHEMICAL RESISTANCE.

COVER: RED/BLUE/YELLOW/GREEN COLOR OF EPDM BLEND COMPOUND. OIL MIST, ABRASION AND WEATHER RESISTANCE.

REINFORCEMENT: HIGH TENSILE SYNTHETIC YARN.

TEMPERATURE: -20°C TO +90°C

SAFETY FACTOR: 3:1

*RMP: EXTRUSION HOSE

*RMPM: MANDREL BUILD HOSE